

TYRES

Product group	Tyres
Item number	10001158
Valid tyre size	6.00 R 9
LI / SI / PR	121 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Sonderpostenkategorie	Remaining stock



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel carcass and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial carcass absorbs unevenness of the surface, thereby increasing driving comfort and safety of the operator and preventing fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

Item number	10001158
EAN	4040658109744
Valid tyre size	6.00 R 9
LI / SI / PR	121 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	16,19
Recommended rim size	4.00
Maximum air pressure [bar].	10,00
Section width (mm)	160
Outer diameter of tyre [mm].	540
Tread depth (mm)	24,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A5	1450	25	Steering wheel	10,00	
	1885	25	Load wheel	10,00	