

TYRES

Product group	Tyres	
Item number	10001162	
Valid tyre size	275 / 80 R 20	
LI / SI / PR	134 K	
TL/TT	TL	
Brand	BKT	
Tread pattern	Multimax MP 540	



Notes and features

- The BKT Multimax MP 540 was developed for multipurpose vehicles in municipality/maintenance applications.
- Thanks to its reinforced, steel belted nylon casing, the tyre provides high load capacity at high speeds.



Technical Informations

Item number	10001162
EAN	8903094071357
Valid tyre size	275 / 80 R 20
Alternative size 1	10.5R20
LI / SI / PR	134 K
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	41,59
Recommended rim size	W9
Permitted rim size	9
Maximum air pressure [bar].	5,20
Section width (mm)	270
Outer diameter of tyre [mm].	955
Stat. radius (SLR) [mm]	443
Rolling circumference [mm].	2913
Tread depth (mm)	14,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 K	2120	110		5,20	