

WHEELS

Product group	Wheels
Item number	10001167
Valid wheel size	600 / 55 R 26.5
Brand	Alliance
Tread pattern	590
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 10000954
LI / SI / PR	173 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	268,15
ECE regulation number	ECE 106
Section width (mm)	611
Stat. radius (SLR) [mm]	611.7

Speed Radius Index (SRI)	675
Rolling circumference [mm].	4071
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	324.07
E-Ready	No
Assembly Item no. Rim	• 33060551
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	6,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade