

## WHEELS

Product group	Wheels
Item number	10001169
Valid wheel size	385 / 55 R 19.5
Brand	Windpower
Tread pattern	WTR 69
Valid rim size	11.75 x 19.5
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3850
Speed complete wheel [km/h]	100



**WINDPOWER**  
Get Your Job Done

## Technical Informations

Assembly Item no. Tyres	• 10466458
LI / SI / PR	156 J, 18 PR
Load capacity 1 [kg]	4000
Speed 1 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	106,73
ECE regulation number	ECE 54 ECE 117

Section width (mm)	384
Stat. radius (SLR) [mm]	423
Rolling circumference [mm].	2827
Tread depth (mm)	15,0
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31267884
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

---

Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade