

## **TYRES**

Product group	Tyres	
Item number	10001172	
Valid tyre size	420 / 70 R 24	
LI / SI / PR	130 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION +	
Sonderpostenkategorie	DOT	
type of damage	DOT	



## Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.



## **Technical Informations**

Item number	10001172
EAN	4040658109867
Valid tyre size	420 / 70 R 24
LI / SI / PR	130 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION +
Antistatic	No
Nettogewicht [kg] (gültig)	81,00
Recommended rim size	13
Permitted rim size	12, 14
Maximum air pressure [bar].	1,60
Section width (mm)	430
Outer diameter of tyre [mm].	1245
Stat. radius (SLR) [mm]	595
Rolling circumference [mm].	3755
Tread depth (mm)	41,7
Tyre capacity 75% [ltr.]	175
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 D	1900	65		1,60	
		65			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.