

TYRES

Product group	Tyres
Item number	10001186
Valid tyre size	205 / 45 R 16
LI / SI / PR	77 T
TL/TT	TL
Brand	Kenda
Tread pattern	Kanine KR20



Notes and features

- The Kenda Kanine KR20 is an ATV radial tyre for use on paved roads.
- It was developed specially for 3-wheeled motorcycles.
- Its tread pattern offers reduced rolling resistance and at the same time excellent lateral traction.
- Deep grooves prevent aquaplaning and provide outstanding performance in rainy conditions.



Technical Informations

Item number	10001186
EAN	4711041536705
Valid tyre size	205 / 45 R 16
LI / SI / PR	77 T
TL/TT	TL
Brand	Kenda
Tread pattern	Kanine KR20
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	8,43
Recommended rim size	6.50J
Permitted rim size	7.00J, 7.50J
Maximum air pressure [bar].	2,18
Section width (mm)	202
Outer diameter of tyre [mm].	588
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
77 T	412	190		2,18	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.