

TYRES

Product group	Tyres	
Item number	10001204	
Valid tyre size	750 / 70 R 26	
LI / SI / PR	158 A8 / 158 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	370	





Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.



Technical Informations

Item number	10001204
EAN	8903635013853
Valid tyre size	750 / 70 R 26
Alternative size 1	28.1R26
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Alliance
Tread pattern	370
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	230,00
Recommended rim size	DW24
Permitted rim size	DW25
Maximum air pressure [bar].	1,60
Section width (mm)	749
Outer diameter of tyre [mm].	1750
Stat. radius (SLR) [mm]	774
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5177
Tread depth (mm)	48,0
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		1,60	
158 B	4250	50		1,60	