

## TYRES

Product group	Tyres
Item number	10001206
Valid tyre size	420 / 85 R 34
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Sonderpostenkategorie	DOT
type of damage	DOT



## Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.

## Technical Informations

Item number	10001206
EAN	4040658110207
Valid tyre size	420 / 85 R 34
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Nettogewicht [kg] (gültig)	110,00
Recommended rim size	15
Permitted rim size	13, 14
Maximum air pressure [bar].	2,40
Section width (mm)	438
Outer diameter of tyre [mm].	1578
Stat. radius (SLR) [mm]	707
Rolling circumference [mm].	4685
Tread depth (mm)	49,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	287
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		2,40	
147 B	3075	50		2,40	