

## RIMS

Product group	Rims
Item number	10001216
Valid rim size	W 14 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-60
Rim colour	Silver
Brand	Jantsa



## Technical Informations

Load capacity of rim 1 [kg]	5300
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	4600
Speed Rims 2 [km/h]	30
Load capacity of rim 3 [kg]	4250
Speed Rims 3 [km/h]	40
Load capacity of rim 4 [kg]	3850
Speed of wheels 4 [km/h].	50
Maximum speed [km/h].	50
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	33,00

<b>Hump</b>	kein Hump
<b>Valve protection</b>	VSH
<b>Single / multi-part</b>	einteilig
<b>Rim material</b>	steel
<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Disc thickness [mm]</b>	10
<b>Knurling</b>	without knurling
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	8
<b>Bolt hole design EUWA</b>	B22 DS 36
<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	221
<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No