

RIMS

Product group	Rims
Item number	10001216
Valid rim size	W 14 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-60
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	5300
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	4600
Speed Rims 2 [km/h]	30
Load capacity of rim 3 [kg]	4250
Speed Rims 3 [km/h]	40
Load capacity of rim 4 [kg]	3850
Speed of wheels 4 [km/h].	50
Maximum speed [km/h].	50
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	33,00

Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No