

TYRES

Product group	Tyres	
Item number	10001229	
Valid tyre size	480 / 65 R 28	
LI / SI / PR	139 A8 / 136 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 65	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	

Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10001229
EAN	4040658110412
Valid tyre size	480 / 65 R 28
LI / SI / PR	139 A8 / 136 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Nettogewicht [kg] (gültig)	91,10
Recommended rim size	15
Permitted rim size	14, 13
Maximum air pressure [bar].	1,60
Section width (mm)	475
Outer diameter of tyre [mm].	1355
Stat. radius (SLR) [mm]	616
Rolling circumference [mm].	4064
Tread depth (mm)	44,0
Lug width (mm)	42
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		1,60	
136 D	2240	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.