

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 10001232            |
| Valid wheel size                  | 4.00 - 4            |
| Brand                             | Kenda               |
| Tread pattern                     | K406                |
| LI / SI / PR                      | 31 A4 / 42 A4, 4 PR |
| TL/TT                             | TT                  |
| Hub design                        | Fork assembly       |
| Type of bearing                   | Ball bearing        |
| Shaft diameter [mm].              | 25                  |
| Mounting length [mm]              | 75                  |
| Hub length [mm]                   | 75                  |
| Rim colour                        | Silver              |
| Load capacity complete wheel [kg] | 150                 |
| Speed complete wheel [km/h]       | 16                  |



## Technical Informations

|                         |                     |
|-------------------------|---------------------|
| Assembly Item no. Tyres | • 19211082          |
| LI / SI / PR            | 31 A4 / 42 A4, 4 PR |
| TL/TT                   | TT                  |
| Brand                   | Kenda               |
| Tread pattern           | K406                |
| Antistatic              | No                  |
| Tyre colour             | Black               |
| ECE regulation number   | ECE 106             |

|                             |                |
|-----------------------------|----------------|
| Maximum air pressure [bar]. | 2,75           |
| Section width (mm)          | 105            |
| Rolling circumference [mm]. | 916.00         |
| Assembly Item no. Rim       | • 39920027     |
| Valid rim size              | 2.50 C - 4     |
| Load capacity of rim 1 [kg] | 400            |
| Speed Rims 1 [km/h]         | 16             |
| Maximum speed [km/h].       | 16             |
| Type of drive               | Towed axle     |
| Hump                        | kein Hump      |
| Single / multi-part         | mehrteilig     |
| Rim material                | steel          |
| RAL                         | RAL9006        |
| Verschweißung beidseitig    | No             |
| Offset hub                  | No             |
| Additional socket required  | No             |
| Valve seat                  | External Valve |
| Valve hole diameter [mm]    | 11.0           |