

TYRES

Product group	Tyres
Item number	10001233
Valid tyre size	600 / 70 R 28
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10001233
EAN	8903094071135
Valid tyre size	600 / 70 R 28
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	174,73
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	611
Tread width (mm)	570
Outer diameter of tyre [mm].	1551
Stat. radius (SLR) [mm]	714
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4667
Tread depth (mm)	57,0
Number of lugs	18x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		2,40	
157 D	4125	65		2,40	