

TYRES

Product group	Tyres	
Item number	10001233	
Valid tyre size	600 / 70 R 28	
LI / SI / PR	160 A8 / 157 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax Factor	





Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.



Technical Informations

Item number	10001233
EAN	8903094071135
Valid tyre size	600 / 70 R 28
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	174,73
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	611
Tread width (mm)	570
Outer diameter of tyre [mm].	1551
Stat. radius (SLR) [mm]	714
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4667
Tread depth (mm)	57,0
Number of lugs	18x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		2,40	
157 D	4125	65		2,40	