

TYRES

Product group	Tyres
Item number	10001234
Valid tyre size	420 / 70 R 24
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10001234
EAN	8903094070947
Valid tyre size	420 / 70 R 24
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,80
Recommended rim size	W13
Permitted rim size	W12, W14L
Maximum air pressure [bar].	2,00
Section width (mm)	418
Outer diameter of tyre [mm].	1248
Stat. radius (SLR) [mm]	563
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3696
Tread depth (mm)	43,0
Number of lugs	20x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A8	2300	40		2,00	
134 D	2120	65		2,00	