

## WHEELS

Product group	Wheels
Item number	10001239
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	TR 313
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-85
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	50
Nettogewicht [kg] (gültig)	43,75
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15710552
LI / SI / PR	116 B, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	50
Maximum air pressure [bar].	3,10
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	370
Stat. radius (SLR) [mm]	342
Rolling circumference [mm].	2233
Tread depth (mm)	23,5
Number of lugs	19x2
Assembly Item no. Rim	• 32010326
Load capacity of rim 1 [kg]	1400
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No

---

Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade