

## WHEELS

Product group	Wheels
Item number	10001240
Valid wheel size	11.5 / 80 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	6
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	2430
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15711784
LI / SI / PR	126 A8 / 139 A8, 14 PR
Load capacity 1 [kg]	1700
Speed 1 [km/h].	40
Load capacity 2 [kg]	2430
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	48.95
ECE regulation number	ECE 106

Section width (mm)	290
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2540
E-Ready	No
Assembly Item no. Rim	• 69050030
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,80
Number of bolt holes	6
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Twin system	Trinker
Twin mounting [inch].	15,3
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve length [mm]	57