

TYRES

Product group	Tyres
Item number	10001244
Valid tyre size	REIFEN VF 600 / 60 R 30
LI / SI / PR	147 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib
Sonderpostenkategorie	DOT
type of damage	DOT



Notes and features

- Below 1 bar consistent low inflation pressure up to 65 km/hl
- Low soil compaction as a result.

- Saving fuel and time.
- High braking safety and steering precision.



Technical Informations

Item number	10001244
EAN	4040658110559
Valid tyre size	REIFEN VF 600 / 60 R 30
LI / SI / PR	147 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib
Antistatic	No
Nettogewicht [kg] (gültig)	141,50
Recommended rim size	20
Maximum air pressure [bar].	1,00
Section width (mm)	603
Outer diameter of tyre [mm].	1493
Stat. radius (SLR) [mm]	633
Rolling circumference [mm].	4379
Tread depth (mm)	50,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	382
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 D	3075	65		1,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.