Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	10001245	
Valid tyre size	REIFEN 600 / 70 R 30	
LI / SI / PR	158 D	
TL/TT	TL	
Brand	Michelin	
Tread pattern	MachXBib	
Sonderpostenkategorie	DOT	
type of damage	DOT	



Notes and features

- Super-wide tyre for upper performance class.
- Specially designed for gentle soil tillage.

• Suitable for heavy road transport.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001245
EAN	4040658110566
Valid tyre size	REIFEN 600 / 70 R 30
LI / SI / PR	158 D
TL/TT	TL
Brand	Michelin
Tread pattern	MachXBib
Antistatic	No
Nettogewicht [kg] (gültig)	200,00
Recommended rim size	DW20B
Permitted rim size	DW18L, DW21B
Maximum air pressure [bar].	2,40
Section width (mm)	638
Outer diameter of tyre [mm].	1604
Stat. radius (SLR) [mm]	737
Rolling circumference [mm].	4760
Tread depth (mm)	56,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	468
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.