

## TYRES

|                 |                           |
|-----------------|---------------------------|
| Product group   | Tyres                     |
| Item number     | 10001259                  |
| Valid tyre size | 245 / 70 R 17.5           |
| LI / SI / PR    | 143 / 141 L (146 / 146 F) |
| TL/TT           | TL                        |
| Brand           | Semperit                  |
| Tread pattern   | Runner T3                 |



Bohnenkamp  
■ ■ ● Moving Professionals

**SEMPERIT**   
Seit 1906.

## Notes and features

- The Semperit Runner T3 is a truck trailer tyre for local and long-distance traffic.
- Its particularly wide tread and the cut-resistant rubber compound ensure slow wear and a long service life.
- Over its entire service life, the tyre offers very good wet grip.
- Thanks to its sipes, the tyre offers excellent performance all year round, even in winter road conditions.

## Technical Informations

|                              |                           |
|------------------------------|---------------------------|
| Item number                  | 10001259                  |
| EAN                          | 4024067004067             |
| Valid tyre size              | 245 / 70 R 17.5           |
| LI / SI / PR                 | 143 / 141 L (146 / 146 F) |
| TL/TT                        | TL                        |
| Brand                        | Semperit                  |
| Tread pattern                | Runner T3                 |
| M+S                          | M+S                       |
| 3PMSF                        | 3PMSF                     |
| Axle position truck          | TR                        |
| Rolling resistance           | C                         |
| Wet grip                     | C                         |
| Rolling noise [db].          | 71                        |
| Rolling noise level          | A                         |
| Antistatic                   | No                        |
| Tyre colour                  | Black                     |
| ECE regulation number        | ECE 54,ECE 117            |
| Nettogewicht [kg] (gültig)   | 31,90                     |
| Recommended rim size         | 6.75                      |
| Maximum air pressure [bar].  | 9,50                      |
| Section width (mm)           | 240                       |
| Tread width (mm)             | 198                       |
| Outer diameter of tyre [mm]. | 807                       |
| Stat. radius (SLR) [mm]      | 373                       |
| Rolling circumference [mm].  | 2474                      |
| Tread depth (mm)             | 10,9                      |

---

|         |    |
|---------|----|
| E-Ready | No |
|---------|----|

---

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 L | 2725               | 120          | Single        | 9,00                     |              |
| 146 F | 3000               | 80           | Single        | 9,50                     |              |
| 141 L | 2575               | 120          | Twin          | 9,00                     |              |
| 146 F | 3000               | 80           | Twin          | 9,50                     |              |