

TYRES

Product group	Tyres	
Item number	10001259	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	143 / 141 L (146 / 146 F)	
TL/TT	TL	
Brand	Semperit	
Tread pattern	Runner T3	





Notes and features

- The Semperit Runner T3 is a truck trailer tyre for local and long-distance traffic.
- Its particularly wide tread and the cut-resistant rubber compound ensure slow wear and a long service life.
- Over its entire service life, the tyre offers very good wet grin
- Thanks to its sipes, the tyre offers excellent performance all year round, even in winter road conditions.



Technical Informations

Item number	10001259	
EAN	4024067004067	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	143 / 141 L (146 / 146 F)	
TL/TT	TL	
Brand	Semperit	
Tread pattern	Runner T3	
M+S	M+S	
3PMSF	3PMSF	
Axle position truck	TR	
Rolling resistance	С	
Wet grip	С	
Rolling noise [db].	71	
Rolling noise level	A	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 54,ECE 117	
Nettogewicht [kg] (gültig)	31,90	
Recommended rim size	e 6.75	
Maximum air pressure [bar].	9,50	
Section width (mm)	240	
Tread width (mm)	198	
Outer diameter of tyre [mm].	807	
Stat. radius (SLR) [mm]	373	
Rolling circumference [mm].	2474	
Tread depth (mm)	10,9	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 L	2725	120	Single	9,00	
146 F	3000	80	Single	9,50	
141 L	2575	120	Twin	9,00	
146 F	3000	80	Twin	9,50	