# Bohnenkamp Moving Professionals

05.02.2025

### TYRES

Product group	Tyres	
Item number	10001259	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	143 / 141 L (146 / 146 F)	
TL/TT	TL	
Brand	Semperit	
Tread pattern	Runner T3	





#### Notes and features

- The Semperit Runner T3 is a truck trailer tyre for local and long-distance traffic.
- Its particularly wide tread and the cut-resistant rubber compound ensure slow wear and a long service life.
- Over its entire service life, the tyre offers very good wet grip.
- Thanks to its sipes, the tyre offers excellent performance all year round, even in winter road conditions.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10001259
EAN	4024067004067
Valid tyre size	245 / 70 R 17.5
LI / SI / PR	143 / 141 L (146 / 146 F)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner T3
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	31,90
Recommended rim size	6.75
Maximum air pressure [bar].	9,50
Section width (mm)	240
Tread width (mm)	198
Outer diameter of tyre [mm].	807
Stat. radius (SLR) [mm]	373
Rolling circumference [mm].	2474
Tread depth (mm)	10,9

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

05.02.2025

E-Ready

No

#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 L	2725	120	Single	9,00	
146 F	3000	80	Single	9,50	
141 L	2575	120	Twin	9,00	
146 F	3000	80	Twin	9,50	