

TYRES

Product group	Tyres
Item number	10001260
Valid tyre size	VF 750 / 60 R 30.5
LI / SI / PR	187 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa



Notes and features

- The BKT V-Flexa is a radial flotation tyre for heavy agricultural trailers.
- The VF technology (Very High Flexion) enables the same load capacity at up to 30% lower inflation pressure compared with a standard tyre of the same size.
- Thanks to the strong, all-steel casing, the tyre is extremely resistant against punctures and other damages.
- Three additional, heavy-duty steel belt inserts and the reinforced sidewall provide excellent performance.

Technical Informations

Item number	10001260
EAN	8903094073139
Valid tyre size	VF 750 / 60 R 30.5
LI / SI / PR	187 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	283,47
Recommended rim size	AG24.00
Maximum air pressure [bar].	3,20
Section width (mm)	780
Outer diameter of tyre [mm].	1678
Stat. radius (SLR) [mm]	728
Speed Radius Index (SRI)	800
Rolling circumference [mm].	5085
Tread depth (mm)	26,5
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
187 D	9750	65		3,20	