

## TYRES

Product group	Tyres
Item number	10001261
Valid tyre size	750 / 70 R 26
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

## Technical Informations

Item number	10001261
EAN	8903094073146
Valid tyre size	750 / 70 R 26
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	268,18
Recommended rim size	DW25B
Permitted rim size	DW24B
Maximum air pressure [bar].	2,80
Section width (mm)	780
Tread width (mm)	680
Outer diameter of tyre [mm].	1750
Stat. radius (SLR) [mm]	785
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5269
Tread depth (mm)	47,0
Number of lugs	21x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		2,80	
172 B	6300	50		2,80	