

## **TYRES**

Product group	Tyres	
Item number	10001263	
Valid tyre size	235 / 75 R 17.5	
LI / SI / PR	143 / 141 K (144 / 144 F)	
TL/TT	TL	
Brand	Semperit	
Tread pattern	Runner T3	





## Notes and features

- The Semperit Runner T3 is a truck trailer tyre for local and long-distance traffic.
- Its particularly wide tread and the cut-resistant rubber compound ensure slow wear and a long service life.
- Over its entire service life, the tyre offers very good wet arin
- Thanks to its sipes, the tyre offers excellent performance all year round, even in winter road conditions.



## **Technical Informations**

Item number	10001263
EAN	4024067004050
Valid tyre size	235 / 75 R 17.5
LI / SI / PR	143 / 141 K (144 / 144 F)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner T3
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	С
Wet grip	С
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	32,00
Recommended rim size	6.75
Maximum air pressure [bar].	9,50
Section width (mm)	240
Outer diameter of tyre [mm].	807
Stat. radius (SLR) [mm]	373
Rolling circumference [mm].	2474
Tread depth (mm)	10,9
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 K	2725	110	Single	8,80	
144 F	2800	80	Single	9,50	
141 K	2575	110	Twin	8,80	
144 F	2800	80	Twin	9,50	