

WHEELS

Product group	Wheels
Item number	10001267
Valid wheel size	14.0 / 65 - 16
Brand	BKT
Tread pattern	AW 705
Valid rim size	11 x 16
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	49,93
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711834
LI / SI / PR	142 A8, 14 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Maximum air pressure [bar].	4,00
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 106
Section width (mm)	353
Stat. radius (SLR) [mm]	388
Rolling circumference [mm].	2549
Tread depth (mm)	12,0
Assembly Item no. Rim	• 30012034
Load capacity of rim 1 [kg]	2520
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	3550
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21
Bolt hole design EUWA	B18 ES 32
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade