

TYRES

Product group	Tyres
Item number	10001284
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Semperit
Tread pattern	M277



Bohnenkamp
Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit M277 is a trailer tyre for construction site vehicles in mixed or pure construction site use.
- The strong casing is particularly robust and protects against damages.
- The tyre has great self-cleaning properties.

Technical Informations

Item number	10001284
EAN	4024067004784
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Semperit
Tread pattern	M277
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,00
Recommended rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	376
Tread width (mm)	286
Outer diameter of tyre [mm].	1067
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3270
Tread depth (mm)	16,2

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	