

TYRES

Product group	Tyres
Item number	10001290
Valid tyre size	VF 710 / 70 R 42
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Scratcher in the flank





Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.



Technical Informations

Item number	10001290
EAN	4040658110931
Valid tyre size	VF 710 / 70 R 42
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Nettogewicht [kg] (gültig)	332,80
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	1,60
Section width (mm)	731
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	896
Rolling circumference [mm].	6106
Tread depth (mm)	61,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	897
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		1,60	
176 E	7100	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.