

TYRES

Product group	Tyres
Item number	10001294
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Sonderpostenkategorie	Damaged
type of damage	Dismounted, Flap damage



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	10001294
EAN	4040658110979
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Nettogewicht [kg] (gültig)	166,01
Recommended rim size	W16L
Permitted rim size	W15L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	516
Outer diameter of tyre [mm].	1749
Stat. radius (SLR) [mm]	793
Rolling circumference [mm].	5300
Tread depth (mm)	53,5
Number of lugs	21x2
Lug width (mm)	43
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 D	3350	65		1,60	