

TYRES

Product group	Tyres
Item number	10001309
Valid tyre size	480 / 70 R 30
LI / SI / PR	152 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Sonderpostenkategorie	DOT
type of damage	Dismounted,DOT



Technical Informations

Item number	10001309
EAN	4040658111112
Valid tyre size	480 / 70 R 30
LI / SI / PR	152 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	147,00
Recommended rim size	W15L

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Permitted rim size	W14L, W16L
Maximum air pressure [bar].	3,20
Section width (mm)	472
Outer diameter of tyre [mm].	1501
Stat. radius (SLR) [mm]	692
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4561
Tread depth (mm)	51,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65		3,20	