Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------------|------------------------|--|
| Item number | 10001311 | |
| Valid tyre size | 650 / 85 R 38 | |
| LI / SI / PR | 173 D / 170 E | |
| TL/TT | TL | |
| Brand | Firestone | |
| Tread pattern | Maxi Traction | |
| Sonderpostenkategorie | Damaged | |
| type of damage | Dismounted,Stud damage | |



Notes and features

- Agricultural tyre for high-performance tractors. •
- Very good traction in fields.

- Excellent ride comfort on the road. •
- Very low soil compaction. •

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 10001311 |
|------------------------------|---------------|
| EAN | 4040658111129 |
| Valid tyre size | 650 / 85 R 38 |
| LI / SI / PR | 173 D / 170 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Maxi Traction |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 333,40 |
| Recommended rim size | 23 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 701 |
| Outer diameter of tyre [mm]. | 2078 |
| Stat. radius (SLR) [mm] | 940 |
| Rolling circumference [mm]. | 6218 |
| Tread depth (mm) | 63,0 |
| Number of lugs | 21x2 |
| Tyre capacity 75% [ltr.] | 879 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 173 D | 6500 | 65 | | 2,40 | |
| 170 E | 6000 | 70 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.