

TYRES

Product group	Tyres	
Item number	10001318	
Valid tyre size	600 / 65 R 38	
LI / SI / PR	153 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM800	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Puncture at tyre shoulder	



Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort.
- Long service life.



Technical Informations

Item number	10001318
EAN	4040658111174
Valid tyre size	600 / 65 R 38
LI / SI / PR	153 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	168,06
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	590
Outer diameter of tyre [mm].	1745
Stat. radius (SLR) [mm]	785
Rolling circumference [mm].	5210
Tread depth (mm)	55,0
Lug width (mm)	46
Tyre capacity 75% [ltr.]	590
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 D	3650	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.