

TYRES

Product group	Tyres
Item number	10001319
Valid tyre size	620 / 70 R 42
LI / SI / PR	160 D
TL/TT	TL
Brand	Michelin
Tread pattern	OmniBib
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Cut in the flank





Notes and features

- Wide-base tyre of the 70 series for medium-performance tractors.
- Outstanding traction and very good self-cleaning.
- Long service life due to high lugs.
- Excellent ride comfort due to flexible casing.



Technical Informations

Item number	10001319
EAN	4040658111181
Valid tyre size	620 / 70 R 42
LI / SI / PR	160 D
TL/TT	TL
Brand	Michelin
Tread pattern	OmniBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	232,50
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	639
Outer diameter of tyre [mm].	1953
Stat. radius (SLR) [mm]	863
Rolling circumference [mm].	5781
Tread depth (mm)	58,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	658
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.