

TYRES

Product group	Tyres	
Item number	10001325	
Valid tyre size	600 / 65 R 38	
LI / SI / PR	156 A8 / 153 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 65	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Puncture at tyre shoulder	



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10001325
EAN	4040658111242
Valid tyre size	600 / 65 R 38
LI / SI / PR	156 A8 / 153 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	167,15
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	590
Outer diameter of tyre [mm].	1759
Stat. radius (SLR) [mm]	792
Rolling circumference [mm].	5251
Tread depth (mm)	51,0
Lug width (mm)	46
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		1,60	
153 D	3650	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.