

## TYRES

|                       |                               |
|-----------------------|-------------------------------|
| Product group         | Tyres                         |
| Item number           | 10001327                      |
| Valid tyre size       | 520 / 85 R 42                 |
| LI / SI / PR          | 157 D / 154 E                 |
| TL/TT                 | TL                            |
| Brand                 | Firestone                     |
| Tread pattern         | Performer 85                  |
| Sonderpostenkategorie | Damaged                       |
| type of damage        | Dismounted,Crack in the flank |



## Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10001327      |
| EAN                          | 4040658111266 |
| Valid tyre size              | 520 / 85 R 42 |
| LI / SI / PR                 | 157 D / 154 E |
| TL/TT                        | TL            |
| Brand                        | Firestone     |
| Tread pattern                | Performer 85  |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| Nettogewicht [kg] (gültig)   | 240,40        |
| Recommended rim size         | 18            |
| Permitted rim size           | 16            |
| Maximum air pressure [bar].  | 1,60          |
| Section width (mm)           | 561           |
| Outer diameter of tyre [mm]. | 1946          |
| Stat. radius (SLR) [mm]      | 876           |
| Rolling circumference [mm].  | 5838          |
| Tread depth (mm)             | 55,0          |
| Number of lugs               | 22x2          |
| Tyre capacity 75% [ltr.]     | 570           |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 157 D | 4125               | 65           |               | 1,60                     |              |
| 154 E | 3750               | 70           |               | 1,60                     |              |