

TYRES

Product group	Tyres	
Item number	10001328	
Valid tyre size	620 / 70 R 42	
LI / SI / PR	166 D / 163 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Stud damage	



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10001328
EAN	4040658111273
Valid tyre size	620 / 70 R 42
LI / SI / PR	166 D / 163 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	263,40
Recommended rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	640
Outer diameter of tyre [mm].	1966
Stat. radius (SLR) [mm]	889
Rolling circumference [mm].	5898
Tread depth (mm)	57,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	639
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		2,40	
163 E	4875	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.