

## WHEELS

Product group	Wheels
Item number	10001340
Valid wheel size	11.5 / 80 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	103,58
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15711780
LI / SI / PR	123 A8 / 135 A8, 12 PR
Load capacity 1 [kg]	1550
Speed 1 [km/h].	40
Load capacity 2 [kg]	2180
Speed 2 [km/h].	40
Maximum air pressure [bar].	4,10
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
Direction	Right
ECE regulation number	ECE 106
Section width (mm)	290
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2540
Tread depth (mm)	23,0
Assembly Item no. Rim	• 32010185
Load capacity of rim 1 [kg]	3075
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2725
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig

---

Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200570
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade