

WHEELS

Product group	Wheels
Item number	10001348
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	TR 315
Valid rim size	13 x 15
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	50
Nettogewicht [kg] (gültig)	130,03
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15710555
LI / SI / PR	121 B, 10 PR
Load capacity 1 [kg]	1450
Speed 1 [km/h].	50
Maximum air pressure [bar].	4,10
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

Direction	Right
ECE regulation number	ECE 106
Section width (mm)	390
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2320
Tread depth (mm)	20,0
Assembly Item no. Rim	• 39920433
Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2350
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	10
Ventilation holes	No
Single / multi-part	einteilig

Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade