

TYRES

Product group	Tyres
Item number	10001370
Valid tyre size	420 / 85 R 38
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Hole in the flank



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	10001370
EAN	4040658111686
Valid tyre size	420 / 85 R 38
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	131,51
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1679
Stat. radius (SLR) [mm]	760
Rolling circumference [mm].	5060
Tread depth (mm)	50,0
Lug width (mm)	42
Tyre capacity 75% [ltr.]	386
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		1,60	
141 B	2575	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.