

TYRES

Product group	Tyres	
Item number	10001371	
Valid tyre size	420 / 85 R 28	
LI / SI / PR	139 D / 136 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 85	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Hole in the flank	



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10001371
EAN	4040658111693
Valid tyre size	420 / 85 R 28
LI / SI / PR	139 D / 136 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	101,10
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	1,60
Section width (mm)	453
Outer diameter of tyre [mm].	1430
Stat. radius (SLR) [mm]	640
Rolling circumference [mm].	4309
Tread depth (mm)	48,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	262.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 D	2430	65		1,60	
136 E	2240	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.