

TYRES

Product group	Tyres
Item number	10001373
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Michelin
Tread pattern	MultiBib
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Optical defect





Notes and features

- Up to 35% longer service life due to new rubber compound.
- Gentle on the soil due to flexible sidewalls.
- Good traction due to high lugs.
- State-of-the-art sidewall design with an appealing look.



Technical Informations

Item number	10001373
EAN	4040658111716
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Michelin
Tread pattern	MultiBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	226,00
Recommended rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	638
Outer diameter of tyre [mm].	1931
Stat. radius (SLR) [mm]	858
Rolling circumference [mm].	5722
Tread depth (mm)	57,0
Number of lugs	21x2
Lug width (mm)	58
Tyre capacity 75% [ltr.]	646
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.