

TYRES

| | |
|-----------------------|------------------------|
| Product group | Tyres |
| Item number | 10001377 |
| Valid tyre size | VF 600 / 60 R 30 |
| LI / SI / PR | 158 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1060 |
| Sonderpostenkategorie | Damaged |
| type of damage | Dismounted,Stud damage |




TRELLEBORG

Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 10001377 |
| EAN | 4040658111761 |
| Valid tyre size | VF 600 / 60 R 30 |
| LI / SI / PR | 158 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1060 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 140,00 |
| Recommended rim size | 20 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 595 |
| Outer diameter of tyre [mm]. | 1490 |
| Stat. radius (SLR) [mm] | 625 |
| Rolling circumference [mm]. | 4420 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 D | 4250 | 65 | | 1,60 | |