Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10001380	
Valid tyre size	380 / 90 R 50	
LI / SI / PR	151 D	
TL/TT	TL	
Brand	Goodyear	
Tread pattern	OPTITRAC	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Hole in the flank	



Technical Informations

Item number	10001380
EAN	4040658111792
Valid tyre size	380 / 90 R 50
LI / SI / PR	151 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	147,00
Recommended rim size	12

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Maximum air pressure [bar].	2,40
Section width (mm)	394
Outer diameter of tyre [mm].	1958
Stat. radius (SLR) [mm]	897
Speed Radius Index (SRI)	975
Rolling circumference [mm].	5945
Tread depth (mm)	44,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.