

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 10001392 |
| Valid tyre size | VF 600 / 60 R 28 NRO |
| LI / SI / PR | 160 D |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION OPTIMALL |



Notes and features

- The Vredestein Traxion Optimall is an innovative VF tyre for high-performance tractors.
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25% for low soil compaction.
- The upper bead zone is specially reinforced and provides good stability, even at low inflation pressure.
- The strong lug end in the tread centre provides stability, low wear and good self-cleaning properties.
- In on-road use, the tread with a high rubber content ensures slow wear and a long service life.
- The rounded tread contour enables good ride comfort.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 10001392 |
| EAN | 8714692805622 |
| Valid tyre size | VF 600 / 60 R 28 NRO |
| LI / SI / PR | 160 D |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION OPTIMALL |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 162,80 |
| Recommended rim size | DW20B |
| Permitted rim size | DW18L |
| Maximum air pressure [bar]. | 2,00 |
| Section width (mm) | 605 |
| Outer diameter of tyre [mm]. | 1420 |
| Stat. radius (SLR) [mm] | 605 |
| Rolling circumference [mm]. | 4205 |
| Tread depth (mm) | 48,0 |
| Tyre capacity 75% [ltr.] | 388 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 D | 4500 | 65 | | 2,00 | |