

TYRES

Product group	Tyres	
Item number	10001402	
Valid tyre size	425 / 70 - 18	
LI / SI / PR	143 B / 155 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Flotation 647	





Notes and features

- The BKT Flotation 647 is a bias tyre for agricultural vehicles used on soft soil and grasslands
- Due to the wide contact area and the special tread pattern, the pressure on the ground is optimally distributed and the soil is protected
- The flotation tread pattern provides very good selfcleaning properties



Technical Informations

Item number	10001402
EAN	8903094064373
Valid tyre size	425 / 70 - 18
LI / SI / PR	143 B / 155 B
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 647
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	53,02
Recommended rim size	13.00
Maximum air pressure [bar].	3,50
Section width (mm)	435
Outer diameter of tyre [mm].	1065
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 B	2725	50	Drive Wheel	3,50	
155 B	3875	50	Free Rolling	3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.