Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10001404	
Valid tyre size	460 / 85 R 38	
LI / SI / PR	149 A8 / 149 B	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION 85	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Stud damage	





Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range • tractors.
- Its special tread pattern with curved lugs and rounded • shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume • allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring • optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, . high ride comfort and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001404
EAN	4040658111891
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	149,94
Recommended rim size	DW16L
Permitted rim size	W14, DW14L, W15, DW15L
Maximum air pressure [bar].	1,60
Section width (mm)	490
Outer diameter of tyre [mm].	1750
Stat. radius (SLR) [mm]	815
Rolling circumference [mm].	5205
Tread depth (mm)	48,3
Tyre capacity 75% [ltr.]	365
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.