

## **TYRES**

| Product group         | Tyres                  |  |
|-----------------------|------------------------|--|
| Item number           | 10001406               |  |
| Valid tyre size       | 340 / 85 R 28          |  |
| LI / SI / PR          | 127 D / 124 E          |  |
| TL/TT                 | TL                     |  |
| Brand                 | Firestone              |  |
| Tread pattern         | Performer 85           |  |
| Sonderpostenkategorie | Damaged                |  |
| type of damage        | Dismounted,Stud damage |  |



## **Notes and features**

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



## **Technical Informations**

| Item number                  | 10001406      |
|------------------------------|---------------|
|                              |               |
| EAN                          | 4040658111914 |
| Valid tyre size              | 340 / 85 R 28 |
| LI / SI / PR                 | 127 D / 124 E |
| TL/TT                        | TL            |
| Brand                        | Firestone     |
| Tread pattern                | Performer 85  |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| Nettogewicht [kg] (gültig)   | 64,50         |
| Recommended rim size         | 12            |
| Permitted rim size           | 11            |
| Maximum air pressure [bar].  | 1,60          |
| Section width (mm)           | 354           |
| Outer diameter of tyre [mm]. | 1302          |
| Stat. radius (SLR) [mm]      | 585           |
| Rolling circumference [mm].  | 3906          |
| Tread depth (mm)             | 41,0          |
| Number of lugs               | 20x2          |
| Tyre capacity 75% [ltr.]     | 157.5         |
| E-Ready                      | No            |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 127 D | 1750               | 65           |               | 1,60                        |              |
| 124 E | 1600               | 70           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.