Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10001410
Valid tyre size	420 / 85 R 30
LI / SI / PR	140 A8 / 137 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Crack in the tread





Notes and features

- Protects turf and crops due to innovative tread pattern. .
- High load capacity.

- Low soil compaction. •
- Optimal traction. •

05.02.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001410
EAN	4040658111952
Valid tyre size	420 / 85 R 30
LI / SI / PR	140 A8 / 137 B
TL/TT	ть
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	103,24
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1475
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4455
Tread depth (mm)	50,0
Lug width (mm)	41
Tyre capacity 75% [ltr.]	323
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		1,60	
137 B	2300	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.