

TYRES

Product group	Tyres
Item number	10001411
Valid tyre size	480 / 80 R 50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Flap damage



Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.

Technical Informations

Item number	10001411
EAN	4040658111969
Valid tyre size	480 / 80 R 50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	184,00
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	465
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	939
Rolling circumference [mm].	6116
Tread depth (mm)	48,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	479
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		2,40	
159 B	4375	50		2,40	