

TYRES

| | |
|-----------------------|--------------------------------------|
| Product group | Tyres |
| Item number | 10001412 |
| Valid tyre size | 600 / 70 R 28 |
| LI / SI / PR | 157 D / 154 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | MachXBib |
| Sonderpostenkategorie | Damaged |
| type of damage | Dismounted,Puncture at tyre shoulder |



Notes and features

- Super-wide tyre for upper performance class.
- Specially designed for gentle soil tillage.
- Suitable for heavy road transport.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10001412 |
| EAN | 4040658111976 |
| Valid tyre size | 600 / 70 R 28 |
| LI / SI / PR | 157 D / 154 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | MachXBib |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 180,00 |
| Recommended rim size | DW20B |
| Permitted rim size | DW18L, DW21B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 629 |
| Outer diameter of tyre [mm]. | 1571 |
| Stat. radius (SLR) [mm] | 703 |
| Rolling circumference [mm]. | 4666 |
| Tread depth (mm) | 54,0 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 448 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 157 D | 4125 | 65 | | 2,40 | |
| 154 E | 3750 | 70 | | 2,40 | |